



Breaker

TOP205J

18-26ton



JAPAN

POWER

shows the best performance
at various sites of quarry, mining,
general construction, demolition and more.

Exhaustive Quality Control



Access to blow speed adjuster.

Dual greasing points.

Thicker bottom plate

2 Lifting eyes for loading or unloading the breaker from truck.

Auto-lubrication system (option)

Inspection window for retightening the back nuts.

Anti wear steel

No opening on the bracket, every part is plugged.

1. Anti-Blank Fire system
2. Anti-abrasion box style bracket design
3. Blow speed control adjuster
4. High pressure accumulator
5. Auto-lubrication system (option)



SPECIFICATIONS

	Unit	TOP205J
Working Pressure	MPa	15~18
Oil flow Consumption	L/min	110~135
Frequency	b.p.m.	L 360~430
		H 500~560
Operating Weight	kg	1780
Overall Length	mm	2726
Working Steel Dia.	mm	135
Carrier Machine Weight Range	ton	18~26
Carrier Output Flow Range	L/min	140~210

The specifications of breaker are subject to change without notice. These numbers may be varied depending on the carrier machine condition and material.

OKADA AIYON CORPORATION

www.okada-aiyon.com

4-1-18, Kaigan-dori, Minato-ku, Osaka 552-0022, Japan

Tel +81-(0)6-6576-1268 Fax +81-(0)6-6576-1516

Email sales@aiyon.co.jp

[facebook.com/okadaaiyon](https://www.facebook.com/okadaaiyon)

[youtube.com/OkadaAiyonCorp](https://www.youtube.com/OkadaAiyonCorp)

